



COPY OF PAPERS
ORIGINALLY FILED

CERA 237 (10201539)

CERTIFICATE OF MAILING
37 C.F.R. § 1.8

I hereby certify that this correspondence is being deposited with the U.S. Postal Service with sufficient postage as First Class Mail in an envelope addressed to: Assistant Commissioner for Patents, Washington, DC, 20231, on the date below:

6/20/02

Date

Fani Malikouzakis
Name: Fani Malikouzakis

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant(s) : Reiner BINDIG et al.

Application No. : 10/075,558

Filing Date: : February 13, 2002

For: : PIEZOCERAMIC MULTILAYER ACTUATOR WITH A
TRANSITION REGION BETWEEN THE ACTIVE
REGION AND THE INACTIVE HEAD AND FOOT
REGIONS

Commissioner of Patents
and Trademarks
Washington, D.C. 20231

June 20, 2002

PRELIMINARY AMENDMENT

Sir:

Prior to the examiner of this application, please amend the application as follows:

IN THE CLAIMS

Please cancel claims 1-12 without prejudice.

Please add the following new claims 13-25.

- 13. (New) A piezoceramic multilayer actuator comprising an active region, said active region further comprising inner electrodes led out alternately at a surface of said

actuator, wherein, for parallel connection, said inner electrodes of identical polarity of said active region are connected to respective outer electrodes, said outer electrodes being disposed on opposite sides of said actuator; electrode-free piezoelectrically inactive regions further comprising a head region and a foot region; and a transitional region having shrinkage and expansion properties lying between the shrinkage and the expansion properties of said active and inactive regions, said transitional regions interposed between said active region and said respective inactive head and foot regions.--

- 14. (New) The piezoceramic multilayer actuator of claim 13, wherein in said transitional regions, the electrode-to-electrode spacing between the inner electrodes increases in proximity to said inactive regions.--
- 15. (New) The piezoceramic multilayer actuator of claim 14, wherein said increase in spacing of said inner electrodes starts from the spacing of said inner electrodes in said active region and is effected stepwise in a sequence of natural numbers.--
- 16. (New) The piezoceramic multilayer actuator of claim 14, wherein said increase in the spacing of said inner electrodes from said transition region through said head region or foot region starts from the spacing of said inner electrodes in said active region and is effected stepwise in a geometric progression.--
- 17. (New) The piezoceramic multilayer actuator of claim 14, wherein said increase in the spacing of said inner electrodes in said transitional region through said head region or the foot region starts from the spacing of said inner electrodes in said active region and is effected stepwise according to a logarithmic scale.--
- 18. (New) The piezoceramic multilayer actuator of claim 15, wherein the number of steps for increasing the spacing between said electrodes correlates to the

differences between the shrinkage and expansion properties between said active region and at least one of said inactive regions.--

- 19. (New) The piezoceramic multilayer actuator of claim 14, wherein the maximum spacing between the last two electrodes in said transitional region is up to 2 mm.--
- 20. (New) The piezoceramic multilayer actuator of claim 19, wherein said maximum spacing is 0.1 to 1.0 mm.--
- 21. (New) The piezoceramic multilayer actuator of claim 13, wherein said respective transitional regions consist of modified piezoceramic material, the shrinkage and expansion properties of said material lying within the shrinkage and the expansion properties of said active region.--
- 22. (New) The piezoceramic multilayer actuator of claim 21, wherein said properties can be influenced by doping said material with impurity atoms of the materials of the inner electrodes.--
- 23. (New) The piezoceramic multilayer actuator of claim 22, wherein the sintering properties of the material in the transitional region can be influenced by doping said material with impurity atoms of the materials of the inner electrodes.--
- 24. (New) The piezoceramic multilayer actuator of claim 23, wherein said doping exists in a concentration that is produced by natural diffusion in the active region at the boundary between an inner electrode and a ceramic material.--
- 25. (New) The piezoceramic multilayer actuator of claim 22, wherein said doping is effected with silver.--

REMARKS

An early and favorable response is earnestly solicited.

No fee is believed to be ~~due~~, however, should a fee become due the Commissioner is hereby authorized to deduct any fee associated with this filing from Deposit Account No. 500624.

Respectfully submitted,

FULBRIGHT & JAWORSKI L.L.P.

By David Rubin
David Rubin
Reg. No. 40,314

666 Fifth Avenue
New York, NY 10103
Enclosures